



- -20-105°C Operating Temperature
- +- 3% @ 25C
- NTC (10Kohm @ 25C)
- IP65
- Molex Connector
- Media – Liquid, Air, & Gas



DESCRIPTION

The PTS26 temperature sensor was specifically designed for temperature applications in the pool/spa aftermarket and industrial markets. It is fit, form and function equivalent to the Victory 50632201 3 pole temperature sensors. The glass encapsulated NTC allows for protection against water ingress that cause traditional temperature sensors to fail. The simple design can be modified to meet our OEM customers challenging applications. The low cost semi-automated manufacturing process allows for a cost effective solution.

APPLICATIONS


- Process Control
- Automotive
- Pool
- SPAS
- HVAC

Maximum Environmental Ratings

Operating Temperature -20°C to 105°C

Storage Temperature Range -60°C to 125°C

Mechanical Dimensions (inches)



Part Number Configuration

PTS26- 1- 5K

Model — — —

(0= Custom ,1= Molex connector) Connection — — — Ohm Value @25C(5k=5kohms, 25k=25kohm)

Ph: (480) 462-1810 sales@PhoenixSensors.com

Notice:
 Phoenix Sensors LLC reserves the right to make changes to the product contained in this publication. Phoenix Sensors LLC assumes no responsibility for the use of any circuits described herein, conveys no license under any patent or other right, and makes no representation that the circuits are free of patent infringement. While the information in this publication has been checked, no responsibility, however, is assumed for inaccuracies.
 Phoenix Sensors LLC does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of a life-support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications.